

**HEADQUARTERS**

**Cemp srl**  
Via Piemonte 16  
20030 Senago (Milano) - Italy  
Phone: +39 0294435401  
cemp@regalbeloit.com

**OFFICES**

**Germany**  
Dr. Atzinger-Strasse 5  
94036 Passau - Germany  
Phone: +49 (0)8519662320

**France**

14 rue des Cours Neuves,  
77135 Pontcarré - France  
Phone: +33 (0)164668736



**Cemp S.r.l.**

Via Piemonte, 16  
20030 Senago (Milan) - Italy  
Phone: +39 02 94435401

[www.regalbeloit.com](http://www.regalbeloit.com)

**APPLICATION CONSIDERATIONS**

The proper selection and application of power transmission products and components, including the related area of product safety, is the responsibility of the customer. Operating and performance requirements and potential associated issues will vary appreciably depending upon the use and application of such products and components. The scope of the technical and application information included in this publication is necessarily limited. Unusual operating environments and conditions, lubrication requirements, loading supports, and other factors can materially affect the application and operating results of the products and components and the customer should carefully review its requirements. Any technical advice or review furnished by Regal Beloit America, Inc. and/or its affiliates ("Regal") with respect to the use of products and components is given in good faith and without charge, and Regal assumes no obligation or liability for the advice given, or results obtained, all such advice and review being given and accepted at customer's risk.

For a copy of our Standard Terms and Conditions of Sale, please visit <http://www.regalbeloit.com> (please see link at bottom of page to "Standard Terms and Conditions of Sale"). These terms and conditions of sale, disclaimers and limitations of liability apply to any person who may buy, acquire or use a Regal product referred to herein, including any person who buys from a licensed distributor of these branded products.

Regal and Cemp are trademarks of Regal Beloit Corporation or one of its affiliated companies.

©2014, 2018 Regal Beloit Corporation, All Rights Reserved. MCB18049E • Form# 10225E



# ATEX - IECEx

MOTORS FOR HAZARDOUS LOCATIONS

**REGAL**<sup>®</sup>

**REGAL**<sup>®</sup>

# A COMPREHENSIVE RANGE OF MOTORS FOR HAZARDOUS AREAS

## T Y P E O F M O T O R

## M A I N O P T I O N S



### FLAMEPROOF ELECTRIC MOTORS

**E3.../E4A... SERIES - IE3/IE4  
GAS & DUST VERSION**

- According to standards:
  - IEC/EN 600079-0, 1, 7, 31
  - IEC 60034-1, 2, 5, 6, 7, 8, 9, 12, 14, 30
  - IEC 60072
- Ex db, Ex db eb, Ex tb, Ex tc
  - \* Terminal box Ex db or Ex eb available
  - \* Continuous duty or intermittent duty
- Atex category I M2, II2G, II2D, II2GD
- Gas group I, IIB, IIC
- Dust group IIIB, IIIC
- Temperature classes T3, T4, T5, T6
- Surface temperature classes (Dust) T150°C - T135°C - T125°C - T100°C - T85°C
- Protection IP55, IP56, IP65, IP66
- Frame size from 80 to 355 (IEC)
- Power 0,75 - 375 kW
- 400V, 50Hz (multi voltage 380-400-415V/50Hz and 460V/60Hz)
- Pole 2, 4, 6, 8
- Self-cooling (IC411); Forced cooling (IC416); Not ventilated (IC410); Totally enclosed air over (IC418)
- Premium efficiency IE3; Super-premium efficiency IE4 Available IE1/IE2 (A Series)
- Certified ATEX and IECEx
- Certified GMEE



### FLAMEPROOF ELECTRIC MOTORS WITH BRAKE

**E3.../E4D SERIES - IE3/IE4  
GAS & DUST VERSION**

- According to standards:
  - IEC/EN 600079-0, 1, 7, 31
  - IEC 60034-1, 2, 5, 6, 7, 8, 9, 12, 14, 30
  - IEC 60072
- Motor enclosure Ex db (flameproof) and brake in separate Ex db enclosure
- Terminal box Ex db or Ex eb available
- Multiple choice for brake torque available
- Continuous duty or intermittent duty
- Ex db, Ex db eb, Ex tb, Ex tc
- Atex category II2G, II2D, II2GD
- Gas group IIB, IIC
- Dust group IIIB, IIIC
- Temperature classes T3, T4, T5, T6
- Surface temperature classes (Dust) T150°C - T135°C - T125°C - T100°C - T85°C
- Protection IP55, IP56, IP65, IP66
- Frame size from 80 to 315 (IEC)
- Power 0,75 - 200 kW
- 400V, 50Hz (multi voltage 380-400-420V/50Hz and 460V/60Hz)
- Pole 2, 4, 6, 8 and dual speed motor (separate windings or Dahlander)
- Self-cooling (IC411); Forced cooling (IC416); Not ventilated (IC410); Totally enclosed air over (IC418)
- Premium efficiency IE3; Super-premium efficiency IE4 Available IE1/IE2
- Certified ATEX and IECEx
- Certified GMEE



### NON SPARKING ELECTRIC MOTORS

**TCN SERIES - IE3/IE4  
GAS & DUST VERSION**

- According to standards:
  - IEC/EN 600079-0, 15, 31
  - IEC 60034-1, 2, 5, 6, 7, 8, 9, 12, 14, 30
  - IEC 60072
- Ex -nA, Ex-tb, Ex-tc
- Atex category II3G, II3G, II3G/II2D, II3GD
- Gas group IIB, IIC
- Dust group IIIB, IIIC
- Temperature classes T3
- Max surface temperature (Dust) T200°C
- Protection IP55, IP56, IP65, IP66
- Frame size from 80 to 355 (IEC)
- Power 0,75 - 375 kW
- 400V, 50Hz and 460V/60Hz
- Pole 2, 4, 6, 8
- Self-cooling (IC411); Forced cooling (IC416); Not ventilated (IC410); Totally enclosed air over (IC418)
- Premium efficiency IE3; Super-premium efficiency IE4 Available IE1/IE2
- Certified ATEX and IECEx
- Certified GMEE



Ex-e increased safety stainless steel terminal box



Brake enclosure



Oversized terminal box



Totally enclosed fan ventilated

### MECHANICAL

- Special flanges and shafts
- Without terminal box with plate (cables gland, or seal joints and conduit)
- Locked bearings, roller bearings or special bearings
- Terminal box on side
- SPM probe (vibrations measurement)
- Double ended shafts
- Cable gland fitted to terminal box
- Condensation drain valve
- Grade A or B vibration
- Rain cap or sun shield water shredding disk
- Low noise
- Auxiliary terminal box
- Low (-60°C) temperature motors

### ELETRICAL

- Special voltage and frequency
- Three phase 2 speeds
- Single phase with permanent capacitor
- Motors for tropical climates
- Electrical special designs
- Class H insulation
- Suitable for frequency converter drives

### ACCESSORIES

- Forced ventilation (IC416)
- Encoders (100 – 10000 ppr)
- Bearing sensors
- Bimetallic thermal protection (NC, NO), thermistors (PTC), platinum resistor(PT100)
- Anti-condensation heaters

### BRAKES

- AC disc brakes
- DC disc brakes
- Brake hand release
- Braking when not energized

### ENGINEERING SERVICES

- Start-up behavior analysis
- Superimposed curve (motor + driven machine)
- Load test and thermal test as per IEC 60034-2-1 (Dynamic method)
- Insulation test
- ATEX, IEC Ex and UL approved for thermal test
- Bureau Veritas and Korean Register approved