

cemp[®]

Flameproof
Motors



TERRAMAX[®] TC SERIES IE3/ IE4 MOTORS MADE IN ITALY

NOVEMBER 2021 | EUROPE



RegalRexnord[™]

TerraMAX[®] TC SERIES MOTORS

IE3 / IE4 MOTORS MADE IN ITALY



TC series motors, built on the global low voltage TerraMAX motor platform, are IE3 & IE4 efficiency totally enclosed fan cooled motors suitable for general industry applications. The TC series motors inherit the premium features of the state of the art TerraMAX motor platform, while delivering energy savings. The rugged construction of the TC series motors meets the industry requirement for all tough and demanding applications. The complete range is manufactured in our Italian plant in Senago, Milan, Italy.

TCI SPECIFICATIONS

Output:	0.75kW to 375kW (1HP to 500HP)
Pole:	2 to 8 pole
Frame:	IEC 80 – 355
Standards:	According to IEC 60034
Power supply:	Available for voltages between 200V to 1000V and frequency 50 or 60Hz
Ambient:	-20°C / +40°C (up to -60°C / +80°C on request)
Construction:	Cast iron with integrally cast feet
Drive Suitability:	Suitable for variable torque duty (10:1)
Terminal box:	Cast iron with special captive screws and metric cable entry
Connection:	Frame 80-112 Star connection, frame 132-355 Delta connection
Insulation:	Class F with class B temperature rise
Thermistors:	PTC included as standard
Protection:	IP55 (up to IP66 on request)
Bearings:	Shielded bearings for frame 80-180
Fan:	Bi-directional fan
Mounting:	All standard mountings B3, B5, B35, V1 (B14 and B34 for frame 80-132)
Certification:	Available efficiency certification GMEE ^{®*} and EAC ^{®*} Declaration
Paint:	RAL 5010 standard

TCN Series (ATEX^{®*} & IECEx^{®*})

Same specifications as the TCI series
II3G Ex ec IIB / IIC T3Gc
Suitable for Zone 2
Certificate Number: TÜV IT 20 ATEX 103X

TCT3 Series (ATEX & IECEx)

Same specifications as the TCI series
II3D Ex tc IIIB / IIIC T150°C - 100°C Dc
Suitable for Zone 22
Certificate Number: TÜV IT 20 ATEX 103X

TCT Series (ATEX & IECEx)

Same specifications as the TCI series
II2D Ex tb / IIIB / IIIC T150°C - 85°C Db
Suitable for Zone 21
Certificate Number: TÜV IT 20 ATEX 078X

TCNT Series (ATEX & IECEx)

Same specifications as the TCI series
II3G, Ex ec, IIB or IIC, T3 Gc (zone 2)
II3D, Ex tc, IIIB or IIIC, T150°C - 100°C Dc
Suitable for Zone 2 + 22
Certificate Number: TÜV IT 20 ATEX 103X

TCE Series (ATEX & IECEx)

Same specifications as the TCI series
II2G, Ex eb, IIC, T3Gb
Suitable for Zone 1
Certificate Number ATEX: DEMKO 18 ATEX 2068X
Certificate Number IECEx: IECEx UL 17.0104X

PERFORMANCE DATA

Motor Frame	Pn [kW]	n [1/min]	In (A)	Efficiency [%]	Cos. Φ	Mn [Nm]	Ia/In	Ma/Mn	Mm/Mn	Noise level [dB(A)]	Moment of inertia [kgm ²]	Weight (kg)	
2 POLE MOTORS													
TC.. 80MA 2	0.75	2865	1.59	81.4	0.83	2.50	7.0	2.7	3.4	73	65	0.0010	18.7
TC.. 80MB 2	1.1	2861	2.31	83.0	0.81	3.67	7.6	3.5	3.5	73	65	0.0012	19.8
TC.. 90S 2	1.5	2870	3.04	84.8	0.84	4.99	7.8	2.0	3.7	76	68	0.0017	25.6
TC.. 90L 2	2.2	2866	4.33	86.2	0.86	7.33	8.4	2.9	3.6	76	68	0.0021	28.7
TC.. 100LA 2	3	2879	5.73	87.2	0.89	9.95	8.4	3.6	3.9	78	70	0.0031	39.3
TC.. 112M 2	4	2903	7.27	88.1	0.89	13.16	8.4	2.1	3.5	81	73	0.0081	44.7
TC.. 132SA 2	5.5	2924	10.2	89.2	0.86	17.96	8.1	2.4	3.5	84	75	0.0142	70.9
TC.. 132SB 2	7.5	2920	13.5	90.1	0.88	24.53	6.7	2.1	3.5	84	75	0.0169	77.3
TC.. 160MB 2	11	2951	19.9	91.2	0.88	35.60	7.9	2.3	3.6	84	76	0.0553	135.0
TC.. 160MC 2	15	2944	26.4	91.9	0.89	48.65	8.2	2.2	3.5	84	76	0.0689	150.0
TC.. 160LA 2	18.5	2944	32.3	92.4	0.90	60.01	8.2	2.5	3.5	84	76	0.0808	163.0
TC.. 180M 2	22	2963	38.7	92.7	0.88	70.90	7.8	2.1	3.4	81	72	0.1265	211.0
TC.. 200LA 2	30	2973	54.3	93.3	0.85	96.36	7.5	2.1	3.3	89	79	0.2245	272.0
TC.. 200LB 2	37	2973	65.5	93.7	0.87	118.8	7.4	2.1	3.1	89	79	0.2541	291.0
TC.. 225MA 2	45	2966	78.7	94.4	0.87	144.9	6.9	2.2	3.1	89	79	0.3641	379.0
TC.. 250M 2	55	2981	93.3	94.3	0.90	176.2	7.5	1.8	3.2	87	77	0.6229	492.0
TC.. 280S 2	75	2982	126.5	94.8	0.90	240.2	7.5	1.8	3.2	90	79	1.0493	698.0
TC.. 280MA 2	90	2981	150.9	95.0	0.90	288.3	7.3	1.8	3.0	90	79	1.1238	718.0
TC.. 315S 2	110	2983	186.4	95.3	0.89	352.1	6.9	1.7	3.0	95	84	1.9059	963.0
TC.. 315MB 2	132	2983	223.7	95.5	0.89	422.6	7.1	1.8	3.1	95	84	2.0265	1007.0
TC.. 315LA 2	160	2983	269.9	95.7	0.89	512.2	7.1	1.8	3.0	95	84	2.2091	1065.0
TC.. 315LC 2	200	2980	338.6	95.8	0.89	640.9	7.1	1.9	3.1	95	84	2.4519	1180.0
TC.. 355M 2	250	2983	425.8	95.8	0.89	800.4	6.8	2.0	2.8	96	85	3.8130	1612.0
TC.. 355MB 2	315	2983	531.9	95.8	0.89	1008.5	6.9	2.1	2.8	96	85	4.4076	1771.0
TC.. 355LB 2	355	2986	601.7	95.8	0.89	1135.4	8.2	2.2	3.2	96	85	4.4075	2002.0
TC.. 355LC 2	375	2986	626.8	96.0	0.90	1199.4	7.9	2.2	3.1	96	85	4.4075	2008.0
4 POLE MOTORS													
TC.. 80MB 4	0.75	1428	1.70	82.9	0.77	5.02	6.3	2.8	2.8	62	56	0.0018	22.5
TC.. 90S 4	1.1	1444	2.42	84.5	0.78	7.27	7.2	3.0	3.4	67	61	0.0031	27.3
TC.. 90L 4	1.5	1441	3.23	85.6	0.78	9.94	7.4	3.2	3.5	67	61	0.0037	29.8
TC.. 100LA 4	2.2	1457	4.51	86.9	0.81	14.42	8.0	2.7	3.2	69	62	0.0096	39.7
TC.. 100LB 4	3	1455	5.87	87.8	0.83	19.69	8.2	2.9	3.3	69	62	0.0109	43.9
TC.. 112MB 4	4	1451	7.66	88.7	0.82	26.32	8.3	2.7	3.1	70	62	0.0174	52.3
TC.. 132S 4	5.5	1463	10.8	89.6	0.82	35.90	6.9	2.0	2.8	73	65	0.0363	80.9
TC.. 132M 4	7.5	1462	14.4	90.4	0.83	48.99	6.8	2.1	2.7	73	65	0.0428	88.7
TC.. 160MB 4	11	1476	20.7	91.4	0.84	71.17	7.3	2.4	3.2	74	66	0.1080	150.0
TC.. 160LA 4	15	1472	27.8	92.1	0.85	97.31	7.5	2.5	3.2	74	66	0.1368	170.0
TC.. 180M 4	18.5	1477	35.0	92.6	0.83	119.6	7.1	2.2	3.1	76	67	0.1794	206.0
TC.. 180L 4	22	1474	41.6	93.0	0.82	142.5	7.5	2.4	3.3	76	67	0.2041	222.0
TC.. 200L 4	30	1482	54.2	93.6	0.85	193.3	8.0	2.2	3.1	76	67	0.4379	282.0
TC.. 225S 4	37	1483	67.2	93.9	0.85	238.2	7.1	2.2	2.8	79	68	0.5911	354.0
TC.. 225MA 4	45	1484	80.7	94.2	0.85	289.6	7.5	2.4	2.9	79	68	0.6745	389.0
TC.. 250M 4	55	1488	97.7	94.6	0.86	353.0	7.1	2.0	3.1	83	72	1.4025	517.0
TC.. 280S 4	75	1489	130.4	95.0	0.87	481.0	6.3	2.1	2.5	87	75	2.1833	722.0
TC.. 280MA 4	90	1489	154.7	95.2	0.88	577.2	6.1	2.0	2.4	87	75	2.3954	783.0
TC.. 315S 4	110	1489	193.8	95.5	0.86	705.5	7.1	2.0	3.1	86	72	2.9187	867.0
TC.. 315MB 4	132	1489	230.9	95.6	0.86	846.5	7.3	2.1	3.1	86	72	3.3145	993.0
TC.. 315LA 4	160	1489	275.2	95.9	0.88	1026.1	7.3	2.2	3.1	86	72	3.9566	1165.0
TC.. 315LC 4	200	1489	344.8	96.0	0.87	1282.6	7.2	2.2	3.0	86	72	4.4667	1223.0
TC.. 355M 4	250	1491	428.2	96.0	0.88	1601.3	7.4	2.2	2.5	94	79	7.7973	1692.0
TC.. 355LB 4	315	1491	534.1	96.0	0.89	2017.6	7.2	1.9	2.4	94	79	9.6454	1879.0
TC.. 355LC 4	355	1491	602.7	96.0	0.89	2273.8	7.3	2.0	2.3	94	79	10.0240	1953.0
TC.. 355LD 4	375	1490	629.8	96.0	0.90	2402.8	7.0	1.9	2.2	94	79	10.3940	1972.0

Continued on next page.

PERFORMANCE DATA

Motor Frame	Pn [kW]	n [1/min]	In (A)	Efficiency [%]	Cos. Φ	Mn [Nm]	Ia/In	Ma/Mn	Mm/Mn	Noise level [dB(A)]	Moment of inertia [kgm ²]	Weight (kg)	
6 POLE MOTORS													
TC.. 90S 6	0.75	961	2.02	79.1	0.65	7.47	6.0	2.9	3.4	68	60	0.0032	28.0
TC.. 90L 6	1.1	941	2.84	81.0	0.67	11.19	5.4	3.2	3.2	68	60	0.0040	29.7
TC.. 100L 6	1.5	966	3.62	82.5	0.72	14.83	6.6	2.6	3.1	70	62	0.0127	37.8
TC.. 112M 6	2.2	958	5.04	84.3	0.75	21.93	6.5	2.7	3.0	70	62	0.0148	48.2
TC.. 132S 6	3	970	6.60	85.6	0.77	29.60	5.6	1.9	2.4	73	65	0.0358	66.3
TC.. 132M 6	4	973	8.68	86.8	0.77	39.26	6.0	2.1	2.6	73	65	0.0450	75.9
TC.. 132MB 6	5.5	973	11.8	87.6	0.77	53.98	6.3	2.3	2.7	73	65	0.0536	86.0
TC.. 160M 6	7.5	976	14.9	89.1	0.82	73.39	5.6	1.8	2.5	75	67	0.1374	140.0
TC.. 160LB 6	11	977	21.9	90.0	0.78	107.5	5.9	2.1	2.7	75	67	0.1907	163.0
TC.. 180L 6	15	982	29.7	91.2	0.80	145.9	7.0	2.4	2.9	80	71	0.2874	222.0
TC.. 200LA 6	18.5	984	36.6	91.7	0.80	179.6	6.3	2.1	2.6	80	71	0.5182	262.0
TC.. 200LB 6	22	985	42.9	92.2	0.80	213.4	5.9	2.0	2.5	80	71	0.6079	275.0
TC.. 225MA 6	30	987	55.9	92.9	0.83	290.3	6.8	2.1	2.8	79	70	0.8966	374.0
TC.. 250M 6	37	987	68.4	93.3	0.84	357.3	6.6	2.2	2.7	81	71	1.5698	490.0
TC.. 280S 6	45	989	84.1	93.7	0.82	434.5	6.0	1.7	2.5	83	72	2.1714	599.0
TC.. 280MA 6	55	989	100.9	94.1	0.84	531.1	6.0	1.8	2.4	83	72	2.3543	648.0
TC.. 315S 6	75	989	139.0	94.6	0.82	724.2	6.0	1.8	2.4	83	70	3.2215	812.0
TC.. 315MA 6	90	990	168.2	95.0	0.82	868.2	6.1	1.9	2.0	83	70	3.7478	877.0
TC.. 315LA 6	110	990	202.9	95.3	0.82	1061.1	6.4	2.0	2.5	83	70	4.5367	973.0
TC.. 315LC 6	132	990	244.2	95.5	0.82	1273.3	6.5	2.1	2.5	83	70	5.1945	1121.0
TC.. 355MA 6	160	992	274.5	96.0	0.88	1540.3	6.7	2.0	2.7	90	75	8.2873	1577.0
TC.. 355MB 6	200	992	362.4	95.8	0.83	1925.3	6.8	2.1	2.7	90	75	9.3705	1710.0
TC.. 355LB 6	250	992	454.0	95.8	0.83	2406.8	6.9	2.0	2.7	90	75	11.1050	1875.0
8 POLE MOTORS													
TC.. 100LA 8	0.75	721	2.06	75.0	0.70	9.88	5.1	1.9	2.7	63	56	0.0136	43.5
TC.. 100LB 8	1.1	719	2.88	77.7	0.71	14.9	5.0	1.9	2.6	63	56	0.0161	43.5
TC.. 112M 8	1.5	710	3.74	79.7	0.73	20.1	5.0	1.8	2.3	63	56	0.0315	55.4
TC.. 132S 8	2.2	725	5.38	81.9	0.72	29.5	5.0	1.8	2.3	66	59	0.0603	76.2
TC.. 132M 8	3	725	7.19	83.6	0.72	39.4	5.0	1.8	2.3	66	59	0.0716	87.3
TC.. 160MB 8	4	730	9.45	85.0	0.72	53.8	5.3	1.7	2.3	68	60	0.1290	161.0
TC.. 160MC 8	5.5	730	12.6	86.5	0.73	73.4	5.3	1.7	2.3	68	60	0.1640	161.0
TC.. 160L 8	7.5	728	16.7	87.8	0.74	98.0	5.4	1.8	2.2	68	60	0.1990	187.5
TC.. 180LA 8	11	730	23.7	89.3	0.75	147	6.4	1.7	2.6	72	64	0.3250	255.3
TC.. 200LA 8	15	739	32.9	90.4	0.73	193	5.5	1.9	2.5	72	64	0.7390	301.3
TC.. 225S 8	18.5	738	37.1	91.1	0.79	241	5.2	1.7	2.2	71	63	0.8750	430.1
TC.. 225MA 8	22	738	43.4	91.5	0.80	290	5.2	1.7	2.2	71	63	1.0380	430.1
TC.. 250MA 8	30	739	58.0	92.4	0.81	386	5.3	1.8	2.2	73	64	2.1990	563.5
TC.. 280S 8	37	742	71.9	92.9	0.80	480	5.8	1.8	2.2	75	65	3.4620	688.9
TC.. 280M 8	45	742	87.4	93.5	0.80	576	5.6	1.8	2.2	75	65	3.7390	745.2
TC.. 315SA 8	55	742	115	92.5	0.75	720	5.2	1.7	2.2	75	63	3.8320	933.8
TC.. 315SB 8	75	743	154	93.1	0.75	960	5.3	1.8	2.2	75	63	4.8690	933.8
TC.. 315SC 8	90	743	184	93.4	0.76	1151	5.4	1.9	2.2	75	63	5.7120	933.8

OPTIONS AVAILABLE FOR TERRAMAX[®] TC MOTORS SERIES

Electrical

- Special voltages up to 1000V
- Special frequencies
- Resistance Temperature Detectors PT100
- PTC Thermistors
- Anti-condensation heaters
- Tropicalized windings
- Electrical special designs
- Class H insulation
- Three phase 2 speeds

Accessories

- Suitable for frequency converter drives
- Forced ventilation (IC416)
- Encoders (100 – 10000 PPR)
- Bearing sensors
- Suitable for AC drives

Mechanical

- Protection IP55, IP56, IP65, IP66
- Special flanges and shafts
- Locked, roller or special bearings
- SPM probe (vibrations measurement)
- Cable gland fitted to terminal box
- Double ended shafts
- Condensation drain holes
- Vibration level grade A or B / IEC 60034-14
- Rain cap or sun shield
- Water protection disk
- Auxiliary terminal box



ITALY

Cemp s.r.l.
Via Piemonte 16 Senago
Milano Italy
T: +39 0294435401
cemp@regalrexnord.com

GERMANY

Cemp International GmbH
Dr. Atzinger- Strasse 5
Passau Germany
T: +49 (0) 8519662320
cemp-germany@regalrexnord.com

FRANCE

Cemp
Richard Chalhoub
M: +39 348 4353825
Richard.Chalhoub@regalrexnord.com

APPLICATION CONSIDERATIONS

The proper selection and application of motors and components, including the related area of product safety, is the responsibility of the customer. Operating and performance requirements and potential associated issues will vary appreciably depending upon the use and application of such products and components. The scope of the technical and application information included in this publication is necessarily limited. Unusual operating environments and conditions, lubrication requirements, loading supports, and other factors can materially affect the application and operating results of the products and components and the customer should carefully review its requirements. Any technical advice or review furnished by Regal Rexnord Corporation and its affiliates with respect to the use of products and components is given in good faith and without charge, and Regal Rexnord assumes no obligation or liability for the advice given, or results obtained, all such advice and review being given and accepted at customer's risk.

For a copy of our Standard Terms and Conditions of Sale, please visit <http://www.regalrexnord.com> (please see link at bottom of page to "Standard Terms and Conditions of Sale"). These terms and conditions of sale, disclaimers and limitations of liability apply to any person who may buy, acquire or use a Regal Rexnord product referred to herein, including any person who buys from a licensed distributor of these branded products.

The following trademarks are not owned by or under the control of Regal Rexnord Corporation: GMEE is a trademark or trade name of IEC System for Conformity testing and Certification of Electrotechnical Equipment; EAC is a trademark or trade name of Eurasian Customs Union, IECex is a trademark or trade name of International Electrotechnical Commission, ATEX is a trademark or trade name of European Committee for Standardization.

Regal Rexnord, Cemp and TerraMAX are trademarks of Regal Rexnord Corporation or one of its affiliated companies.
©2020, 2021 Regal Rexnord Corporation, All Rights Reserved. MCB21008E • Form# 10383E